


Light Duty Cantilever Capacity Chart: **For Hand Loading Only!**


UPRIGHTS

Upright Tower Heights	Arm Length	Column Type / Capacity Per Side		
		LSUBG / LDUBG	LSUBB / LDUBB	LSUBW / LDUBW
72"	12"	5,000#	5,800#	6,400#
	18"	4,000#	4,600#	5,100#
	24"	3,500#	3,900#	4,300#
84"	12"	4,600#	5,450#	6,100#
	18"	3,850#	4,450#	4,950#
	24"	3,350#	3,750"	4,150#
96"	12"	4,200#	5,100#	5,800#
	18"	3,700#	4,300#	4,800#
	24"	3,200#	3,600#	4,000#
108"	12"	3,750#	4,550#	5,200#
	18"	3,450#	4,050#	4,500#
	24"	3,100#	3,400#	3,800#
120"	12"	3,300#	4,000#	4,600#
	18"	3,200#	3,800#	4,200#
	24"	3,000#	3,200#	3,600#

Double-Sided
Upright



Single-Sided
Upright



ARMS

	Arm Length	Straight Arm Model Number	Inclined Arm Model Number	Capacity
	12"	LSA-XG012	LIA-XG012	500#
	18"	LSA-XG018	LIA-XG018	500#
	24"	LSA-XG024	LIA-XG024	500#



8/18/2014

Light Duty Cantilever Capacity Chart: **For Hand Loading Only!**

BRACING (Now Sold Individually)

Upright Height	Horizontal Bracing Dimension				
	24"	30"	36"	42"	48"
72"	LHBL1024 (2 REQ'D/BAY)	LHBL1030 (2 REQ'D/BAY)	LHBL1036 (2 REQ'D/BAY)	LHBL1042 (2 REQ'D/BAY)	LHBL1048 (2 REQ'D/BAY)
84", 96", 108", 120"	LHBL1024 (3 REQ'D/BAY)	LHBL1030 (3 REQ'D/BAY)	LHBL1036 (3 REQ'D/BAY)	LHBL1042 (3 REQ'D/BAY)	LHBL1048 (3 REQ'D/BAY)

Upright Height	54"	60"	66"	72"
72"	LHBL1054 (2 REQ'D/BAY)	LHBL1060 (2 REQ'D/BAY)	LHBL1066 (2 REQ'D/BAY)	LHBL1072 (2 REQ'D/BAY)
84", 96", 108", 120"	LHBL1054 (3 REQ'D/BAY)	LHBL1060 (3 REQ'D/BAY)	LHBL1066 (3 REQ'D/BAY)	LHBL1072 (3 REQ'D/BAY)